

airconditioning & refrigeration solutions sales | repairs | services

@ GREE

GREE Clivia

























J., Auto



%



1-1-





Turbo



8°C\\\

1





LCD

Smart humidity control

It is the first time that Gere combines temperature, humidity, and energy efficiency variables to form the optimal temperature and humidity curve of human body with energy saving and select the most comfortable humidity range so that comfort and energy saving can be available by the users at the same time:



Clothes drving function

Clivia is specially designed with the continuous dehumidification function, which can meet the daily need for drying clothes. User doesn't need to place a dehumidifier at home and just an air conditioner can achieve both cooling and clothes drying.




UVC Sterilization

Use UVC to continuously irradiate the evaporator and the air passing through it to effectively remove multiple bacteria for comprehensive and efficient sterilization.

Al for maximum efficiency

Clivia is the world's first air conditioner with G-AI, an artificial intelligence system. It learns user habits to optimize energy savings and ensure comfort throughout the room. Save up to 10% on energy consumption annually with Clivia's intelligent algorithm.





GREE











		TECH	HNICAL SPECIFICATIONS		
			CLIVIA12	CLIVIA18	CLIVIA24
COOLING CAPACITY (MIN - NOM - MAX)		kW	0.90 - 3.15 - 4.40	0.85 - 5.30 - 6.30	1.80 - 7.10 - 7.80
COOLING CAPACITY (MAX)		BTU/h	15012.8	21496	26614
HEATING CAPACITY (MIN - NOM - MAX)		kW	0.90 - 3.81 - 4.70	1.05 - 5.35 - 7.00	1.50 - 7.30 - 9.40
HEATING CAPACITY (MAX)		BTU/h	16036.4	23884	32073
PDESIGNC		kW	3.5	5.3	7.1
EER/COP		W/W	3.55/3.9	3.35/3.84	3.51/3.9
SEER/SCOP		-	7.2/4.1	7.3/4.2	7/4.3
ENERGY CLASS			A++/A+++	A++/A+++	A++/A+++
AIR FLOW VOLUME (SS, H, MH, M, ML, L, SL)		m³/h	680/620/560/490/450/420/390	1000/850/760/650/580/520/450	1000/850/760/580/520/450/40
DEHUMIDIFICATION		L/h	1.4	1.9	2.4
POWER SUPPLY		V/Ph/Hz	220-240~/1/50	220-240~/1/50	220-240~/1/50
POWER INPUT	COOLING	W	989	1582	2030
	HEATING	W	977	1393	1870
CURRENT INPUT	COOLING	A	4.4	7.2	9
	HEATING	A	4.4	6.3	9.3
RATED CURRENT	COOLING	A	7.4	10.5	14
MAX. DISTANCE	LENGTH	m	15	25	25
WAX. DISTANCE	HEIGHT	m	10	10	10
OUTDOOR UNIT			GWH12AUCXB-K6DNA1A/O	GWH18AUDXD-K6DNA1A/O	GWH24AUDXF-K6DNA1A
NET DIMENSIONS(W x H x D)		mm	732x555x330	802x555x350	958x660x402
NET/GROSS WEIGHT		Kg	25.5/28	31.5/34	45/49.5
SOUND PRESSURE LEVEL/SOUND POWER LEVEL		dB(A)	52/63	56/65	59/70
ADDITIONAL GAS CHARGE		g/m	16	16	40
REFRIGERANT TYPE			R32	R32	R32
REFRIGERANT CHARGE		kg	0.57	0.85/30	1.4
LIQUID PIPE DIAMETER/GAS PIPE DIAMETER		inch	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5,8"
MAX. PIPE LENGTH WITHOUT ADDITIONAL CHARGE		m	5	5	5
OPERATION RANGE FOR COOLING/HEATING		C°	15 ~ 50/-25 ~ 30	15 ~ 50/-25 ~ 30	15 ~ 50/-25 ~ 30
INDOOR UNIT			GWH12AUCXB-K6DNA1A/I	GWH18AUDXD-K6DNA1A/I	GWH24AUDXF-K6DNA1A
REFRIGERANT TYPE			R32	R32	R32
NET DIMENSIONS(W x H x D)		mm	837x293x200	993x311x222	993x311x222
NET/GROSS WEIGHT		Kg	9.5/11.5	12.5/15	13/15.5
SOUND PRESSURE LEVEL (SS/H/MH/M/ML/L/SL)		dB(A)	41/38/36/33/30/29/27/26/25/19	48/45/44/42/40/37/36/35/34/32/29/26/23	50/48/47/44/43/41/40/36/35/33,
SOUND POWER LEVEL (SS/H/MH/M/ML/L/SL)		dB(A)	60/55/52/50/47/44/43/41/40/39/33	60/57/55/53/50/49/48/47/45/42/39/36	65/64/62/59/58/56/55/53/57/50/4

*Gree reserves the right to modify the specifications without prior notice, please confirm the final specifications with sales representatives

WHITE CLIVIA12:

CLIVIA18: €750 €649 €1095 €995

CLIVIA24: €1,295 €1,195

COLOUR CLIVIA12: €795 €695

CLIVIA18: €1,195 €1,095

CLIVIA24: €1,395

€1,295





A: 300, St. Thomas Street Tarxien, TXN1602, MALTA.

M: +356 7989 3193 / T: +356 2789 3193

E: info@cooltekservices.com.mt

W: www.cooltekservices.com.mt