

Air Curtain

The air curtain adopts cross flow blower to generate high speed air flow downward, that be installed upward side of the entrance door or window, to isolate the indoor air from the outdoor air and reduce the loss of indoor cool air, also prevent the insects and dust from entering the indoor environment.



Washable filter



Quiet function



Compact design



Easier maintainability

- Optimized cross-flow fan and good performance motor are adopted.
- Micro processor controlling with high reliability and long service life.
- Anti-corrosion thanks to two-side painted electro-galvanized metal case.
- High quality galvanized steel casing with double-sided plastic spray processing, high anti-corrosion.
- Good strength structure provides powerful airflow.
- Integrated electric components, easy maintenance.
- High performance cross flow fan blade with 3D-optimized streamlined.



Model	Air Curtain	FM-1.25-9-K	FM-1.25-12-K	
Power Supply	Ph, V, Hz	220-230/50	220-230/50	
Power Input		110	140	
Air flow volume	m ³ /h	1200	1650	
Sound Pressure Level (H/L)	dB(A)	59	61	
Dimension (WxDxH)	Outline	mm	900x220x220	1200x220x220
	Package	mm	1015x270x256	1315x270x256
Net Weight/Gross Weight	kg	16/18	20/22	
Loading Quantity	20'GP	sets	848	600
	40'GP/40'HQ	sets	954	746
Setting height	m	2.3~3	2.3~3	
Standard	Wired remote controller	ZY611	ZY611	



A:300, St. Thomas Str. Tarxien, Malta.
M:77893193 / 27893193
E: info@cooltekservices.com.mt
W: www.cooltekservices.com.mt