



GREE Airy A+++

Features: ☐ Standard ☐ Optional



Continuous Heating Technology

Ensure constant-temperature heating for continuously 10h. Say goodbye to temperature fluctuations. Enjoy a seamless and comfortable experience with smaller and negligible temperature difference.

10-Hour

Continuous heating without stop



Defrosting time about
2-3min



AI for maximum efficiency

Airy adopts the AI + intelligent inverter associated control scheme, and pioneers the G-learning intelligent algorithm.

With Gree's independently-developed AI technology, annual power consumption is reduced by 10%!



6-Stage Air Purification



- LEVEL 1 : Dust prevention
- LEVEL 2 : Built-in filtration
- LEVEL 3 : Air inlet UVC sterilization
- LEVEL 4 : Deep evaporator cleaning
- LEVEL 5 : Cold Plasma Air outlet purification
- LEVEL 6 : Self-cleaning of the outdoor unit

Independent Smart Dehumidification

Airy stands out with its smart humidity control, creating a water-retaining film for skin moisture. It caters to user preferences, operates on personalized humidity settings, and includes a continuous dehumidification function, ideal for daily tasks like drying clothes.





TECHNICAL SPECIFICATIONS

			AIRY12	AIRY18	AIRY24
COOLING CAPACITY (MIN - NOM - MAX)		kW	0.85 - 3.50 - 4.50	1.00 - 5.30 - 6.50	1.00 - 7.10 - 8.90
COOLING CAPACITY (MAX)		BTU/h	15354	22178	30366.8
HEATING CAPACITY (MIN - NOM - MAX)		kW	1.00 - 3.81 - 4.90	1.10 - 5.60 - 6.80	1.50 - 7.80 - 9.50
HEATING CAPACITY (MAX)		BTU/h	16718.8	23201.6	32414
PDESIGNC		kW	3.5	5.3	7.1
EER/COP		W/W	4/4	3.6/4.1	4.1/8.5
SEER/SCOP		-	8.5/4.6	8.5/4.6	8.5/4.6
ENERGY CLASS			A+++ / A+++	A+++ / A+++	A+++ / A+++
AIR FLOW VOLUME (SS, H, MH, M, ML, L, SL)		m³/h	720/600/550/470/420/380/310	1100/1000/910/850/790/730/660	1350/1150/1050/950/900/850/800
DEHUMIDIFICATION		L/h	1.4	1.8	2.5
POWER SUPPLY		V/Ph/Hz	220-240~ / 1/50	220-240~ / 1/50	220-240~ / 1/50
POWER INPUT	COOLING	W	875	1472	1868
	HEATING	W	952	1365	1902
CURRENT INPUT	COOLING	A	4.181	6.6	8.7
	HEATING	A	4.548	6.2	9
RATED CURRENT	COOLING	A	7.323	11.5	12.3
MAX. DISTANCE	LENGTH	m	20	25	25
	HEIGHT	m	10	10	10
OUTDOOR UNIT			GWH12AVCXD-K6DNA1A/O	GWH18AVDXE-K6DNA1A/O	GWH24AVEXF-K6DNA1A/O
NET DIMENSIONS(W x H x D)		mm	802x555x350	873x555x376	958x660x402
NET/GROSS WEIGHT		Kg	30/32.5	37/40	42.5/47
SOUND PRESSURE LEVEL/SOUND POWER LEVEL		dB(A)	53/64	59/65	60/70
ADDITIONAL GAS CHARGE		g/m	16	16	40
REFRIGERANT TYPE			R32	R32	R32
REFRIGERANT CHARGE		kg	0.8	0.95	1.4
LIQUID PIPE DIAMETER/GAS PIPE DIAMETER		inch	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
MAX. PIPE LENGTH WITHOUT ADDITIONAL CHARGE		m	5	5	5
OPERATION RANGE FOR COOLING/HEATING		C°	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30
INDOOR UNIT			GWH12AVCXD-K6DNA1A/I	GWH18AVDXE-K6DNA1A/I	GWH24AVEXF-K6DNA1A/I
REFRIGERANT TYPE			R32	R32	R32
NET DIMENSIONS(W x H x D)		mm	907x292x200	970x347x257	1110x347x257
NET/GROSS WEIGHT		Kg	10.5/12.5	15/17.5	17.5/20.5
SOUND PRESSURE LEVEL (SS/H/MH/M/ML/L/SL)		dB(A)	44/38/36/34/31/29/25	45/43/42/41/35/31/28	51/47/44/42/37/35
SOUND POWER LEVEL (SS/H/MH/M/ML/L/SL)		dB(A)	60/52/50/48/45/43/39	60/58/57/56/50/46/43	65/61/58/56/54/51/49

*Gree reserves the right to modify the specifications without prior notice, please confirm the final specifications with sales representatives.

AIRY12: €895 €795

AIRY18: €1,295 €1,195

AIRY24 (color): €1,495 €1,395

AIRY24 (White): €1,395 €1,295

Inc. installation up to 4 mtrs copper

5 YEARS
WARRANTY

+2 YEARS
EXTENDED
WARRANTY

9K to 16K - €60
18K to 24K - €120

A: 300, St.Thomas Street Tarxien, TXN1602, MALTA.

M: +356 7989 3193 / T: +356 2789 3193

E: info@cooltekservices.com.mt

W: www.cooltekservices.com.mt