

GREE T-FRESH



Features: Standard Optional

3D Airflow	LED Display	LCD Display	Auto Fan	Dry Mode	Turbo	Fast Cooling	WiFi Control
Filter Cleaning	Comfortable Sleeping Mode	Intelligent Auto-Restart	Self-cleaning	Wide Voltage Range	Self-Diagnosis	Fire-proof Electric Box	Refrigerant Shortage Protection
3DC Inverter	Soft Start	Anti-cold	Multi-functional Filters	Anti-corrosion Protection of Outdoor Unit	24-hour Timer	X-fan	

airconditioning & refrigeration solutions
sales | repairs | services

Fully-closed air outlet

The air outlet can be completely closed to avoid dust from entering, safeguarding the health of your family



Side filter design

The filter can be drawn from one side. It is easy to detach and clean. Enjoy easy cleaning.



TECHNICAL SPECIFICATIONS

			T-FRESH48	T-FRESH55
COOLING CAPACITY (MIN - NOM - MAX)			kW 1.5 - 12.3 - 13.5	3.4 - 16.0 - 17.2
COOLING CAPACITY (MAX)			BTU/h 46062	58686.4
HEATING CAPACITY (MIN - NOM - MAX)			kW 2.5 - 12.6 - 14.0	4.2 - 17.0 - 19.0
HEATING CAPACITY (MAX)			BTU/h 47768	64828
PDESIGNC			kW 12.3	16
EER/COP			W/W 2.95/3.30	2.91/3.4
SEER/SCOP			- 5.7/3.7	6.1/4.0
ENERGY CLASS			A+/A	A++/A
AIR FLOW VOLUME (SS, H, M, L)			m ³ /h 2000/1850/1700/1580	2400/2200/2000/1800
DEHUMIDIFICATION			L/h 5.0	5.5
POWER SUPPLY			V/Ph/Hz 220-240/50/1	380-415/50/3
POWER INPUT	COOLING	W	4170	5500
	HEATING	W	3820	5000
CURRENT INPUT	COOLING	A	18	8.1
	HEATING	A	16	7.4
RATED CURRENT	COOLING	A	22	11.1
MAX. DISTANCE	LENGTH	m	30	30
	HEIGHT	m	20	20
OUTDOOR UNIT			GVH48ALXH-K6DNC7A/O	GVH55ALXM-M6DNC7A/O
NET DIMENSIONS(W x H x D)			mm 1000x746x427	990x961x427
NET/GROSS WEIGHT			Kg 55/60	97.5/108.5
SOUND PRESSURE LEVEL/SOUND POWER LEVEL			dB(A) 63/73	62/76
ADDITIONAL GAS CHARGE			g/m 40	40
REFRIGERANT TYPE			R32	R32
REFRIGERANT CHARGE			kg 2	2.9
LIQUID PIPE DIAMETER/GAS PIPE DIAMETER			inch 1/4" / 5/8"	3/8" / 5/8"
MAX. PIPE LENGTH WITHOUT ADDITIONAL CHARGE			m 5	5
OPERATION RANGE FOR COOLING/HEATING			C° -15-50 / -15-30	-15-50 / -15-30
INDOOR UNIT			GVH48ALXH-K6DNC7A/I	GVH55ALXM-M6DNC7A/I
REFRIGERANT TYPE			R32	R32
NET DIMENSIONS(W x H x D)			mm 587x1882x394	587x1882x394
NET/GROSS WEIGHT			Kg 53/75	58/70
SOUND PRESSURE LEVEL (SS/H/M/L)			dB(A) 53/51/50/48	57/55/53/52
SOUND POWER LEVEL (SS/H/M/L)			dB(A) 64/61/60/58	67/65/63/62

Gree reserves the right to modify the specifications without prior notice, please confirm the final specifications with sales representatives

***Warranty:**

Residential 5 Years Parts & Labour

Commercial 3 Years Parts & Labour (If maintenance agreement or Service level agreement proof is evident (BT Approved), the client will automatically benefit for an additional 2 years. Otherwise, a standard 3 years warranty on all the above will apply.

A:300, St. Thomas Str. Tarxien, Malta.

M:77893193 / 27893193

E: info@cooltekservices.com.mt

W: www.cooltekservices.com.mt